

HM Digital COM300L Long Probe pH / EC / TDS / Temperature Meter Pro Kit



SKU: HMCOM300L Manufacture warranty period: 12 months Country of Origin: USA The COM-300L is a professional grade level pH/EC/TDS/Temp meter ideal for all water quality testing, hydroponics, water purification applications, wastewater regulation, aquaculture, colloidal silver, labs & scientific testing, pools & spas, ecology testing, boilers & cooling towers, water treatment and more.

Applications:

- Aquaculture
- Aquarium
- Drinking Water
- Food & Beverage
- Hydroponics
- Industrial
- Pool/Spa
- Water Treatment

Features

- Measures Potential Hydrogen (pH), Electrical Conductivity (EC), Total Dissolved Solids (TDS), Salinity and Temperature
- Five scales: pH, μS, mS, ppm 0.5 (NaCl) Scale & 0.7 (442™) Scale
- Automatic Temperature Compensation (ATC) using three temperature coefficients
- Waterproof housing (IP-67 rating)
- Digital Calibration (push button) to any point within the meter's range
- Auto-off function, data-hold function and low-battery indicator
- Display: large and easy-to-read LCD screen includes simultaneous temperature reading
- Replaceable Sensor (model SP-C3)
- Factory Calibrated (pH/EC/TDS)
- Includes translucent cap, 2 (AAA) alkaline batteries, pH 4 & 7 calibration solutions, pH storage solution and lanyard



Specifications:

- рН:
 - Range: 0 14 pH
 - Resolution: 0.1
 - Accuracy: ±0.1 pH
- EC:
 - Range: $0 9990 \mu S$; 0 9.99 mS
 - Resolution:
 - 1µS (0-999);
 - 10µS (1000-9990);
 - 0.01mS (0-9.99).
 - Accuracy: ±2%
- TDS:
 - Range:
 - 0 8560 ppm (0.5 NaCl);
 - 0 5000 ppm (0.7 442)
 - Resolution:
 - 0.1ppm (0-99);
 - 1ppm (100-999);
 - 10ppm (1000-9990)
 - Accuracy: ±2%
- Temperature:
 - o Range: 0~50°C; 32~122°F
 - o Resolution: 1
 - Accuracy: ±1°C/F
- EC to TDS Conversion Factor: Non-linear conversions for KCI, 442TM or NaCl solutions, selected by the user.
- Probe: Detachable platinum electrodes & pH glass sensor with reference tube electrodes
- Housing: IP-67 Waterproof (submersible; floats)
- Power source: 2 x Triple A (AAA) included
- Dimensions: 18.5 x 3.4 x 3.4 cm (7.3 x 1.3 x 1.3 inches)
- Weight: 101.5g (3.6 oz)
- 442 is a registered trademark of the Myron L Company.

Package includes:

- 1 x COM300L meter with translucent cap
- 1 x Packet pH7.0 Buffer Solution (PH-P7)
- 1 x Packet pH4.0 Buffer Solution (PH-P4)
- 1 x Packet pH Electrode Storage Solution
- 1 x Lanyard
- 2 x AAA batteries
- 1 x User's Guide
- 1 x compact portable case



GMM Technoworld Pte Ltd

8 Burn Road #05-01 Trivex Singapore 369977 Tel: 65-6386 1815 Web Site: www.testmeter.sg

