




HM-500

RANGE	pH: 0.0~14.0pH
	EC: 0~9990 μ S/0~20mS
	TDS: 0~9990ppm/ 0~10ppt
	Temp: 0~55°C/ 32~130°F
RESOLUTION	pH: 0.1pH
	EC: 0.1 μ S (0~99.9) 1 μ S (100~999) 10 μ S (1000~9990) 0.01mS (0.01~20.00)
	TDS: 0.1ppm (0~99.9) 1ppm (100~999) 10ppm (1000~9990) 0.01 ppt (0.01~10.00)
	Temp: 0.1°C/°F
ACCURACY	pH: \pm 0.1pH
	EC: \pm 2%
	TDS: \pm 2%
	Temp: \pm 1°C / \pm 1.8°F
CALIBRATION	Digital
POWER	Rechargeable Li-ion Battery
SIZE	20 x 11 x 3.6 cm (8 x 4 x 1.4 in)
WEIGHT	430g/15.1oz



Wall-mount



Bench-top mode



Auto brightness

FEATURES

- Continuous pH (pe) / EC (conductivity) / TDS / temperature monitoring
- Rechargeable battery
- Various usage: Portable / Wall-mount / Bench-top
- Save function: save 20 measurements
- Auto OFF function: 5 minutes
- Alarm: High & Low set value (ON / OFF possible)
- Screen: LCD touch screen (automatic backlight function)
- Sensor: Platinum EC / TDS Sensor, Single Junction pH sensor