

Tenmars TM-204 LUX/FC Light Level Meter up to 200,000 Lux



SKU: TENTM204BK
Manufacture warranty period: 12 months

Display

- 3½ digits LCD with maximum reading 2000.
- Overload indication: "OL".
- Low battery indication

Functions

- According to JISC1609:1993 and CNS 5119 general A class specifications.
- Spectral response close to CIE luminous spectral efficiency.
- Measuring intensities of illumination in Lux or Footcandle.
- Measuring lights source include all visible light sources.
- Cosine angular corrected.
- Many applications include: warehouses, factories, office buildings, restaurants, schools, library, hospitals, photographic, video, parking garages, museums, art galleries, stadiums, building security.



Specifications

• Display: 31/2 digits, 2000 readings

Data hold: YesMax hold: Yes

Zero adjustment: Yes

Sensor: Silicon photo diode and filter

Measuring range:

200, 2000, 20000, 200000 Lux;

o 20, 200, 2000, 20000 Foot-candle

Accuracy:

 +/- 3% (Calibrated to standard incandescent lamp 2856°K and corrected LED day white light),

+/- 8% (other visible light source)

Angle deviation from cosine characteristics:

o 30° +/- 2%,

o 60° +/- 6%,

o 80° +/- 25%

• Meter size (L x W x H): 172 x 55 x 38mm

Sensor size (L x W x H): 80 x 55 x 25

• Weight (including 9V battery): 250g

Standards Certification:

• CE

ROHS

Package includes:

• TM-204

User's Manual

9V battery

Soft carrying case

